

Customer and Installer Information

Provided with Product

Homeowner Information

(Installer information on reverse side)

Care and Cleaning Instructions

Gloss Finish – For normal daily cleaning use a liquid detergent or any foam cleaner such as Dow Bathroom Cleaner. Abrasive cleaners should be avoided, as they will dull the finish. Preserve the luster by occasionally applying a coating of a non-yellowing wax or car wax.

Very minor surface scratches can be buffed out using Dupont polishing compound. Deeper scratches, cigarette burns, or stains can be removed by using Dupont rubbing compound or #600 wet sandpaper lightly in a circular motion. Follow this by buffing with polishing compound to bring back the original gloss.

Matte Finish – On matte finish products you can use any type of household cleaners – abrasive or non-abrasive. Light abrasive cleaners like Soft Scrub will remove most stains and aid in maintaining the appearance of the matte finish. For more stubborn stains, burns, scratches, etc. a green Scotch Brite pad or #600 sandpaper can be used. Because of use and wear over time shiny areas may appear where use is heavy. To bring back the matte finish rub the surface with a green Scotch Brite pad.

Certain chemical substances can harm the surface and should be avoided. Protect the surface from contact with finger nail polish remover, Drano, and other drain cleaners, hydrogen peroxide, hair dyes, paint strippers and all similar products. Caution should be taken with certain brands of curling irons as they may scorch the surface. Decorative items or other articles that sit on light colored cast marble in the same spot for an extended period of time will tend to yellow where they are sitting from a lack of light.

Caution: Excessive hot water could damage the bowl – always mix hot with cold. Keep water temperature below 140°. Manufacturer cannot be responsible for damage to product due to over tightening drain or use of excessive hot water.

Installer Information

(Homeowner information on reverse side)

Do not overtighten drain or damage may result. Use a sealant around the drain - hand tighten and give 1/4 turn with wrench. Do not install tops that are damaged in shipping. Chips or scratches must be reported prior to installation. Please treat as any fine piece of furniture and do not use as a workbench. Abrasions from tools can damage the surface. It is advised that after setting the top the carton be cut out and used to cover the surface deck of the product during the project. All products are carefully inspected and packaged prior to shipment. Proper care during plumbing installation will insure a quality product for our customer.